

In the Claims:

This listing of claims will replace all prior versions, and listings, of claims in this application:

1. (Currently Amended) An integrated pin and clip comprising:

a shaft member;

a locking member located at a first end of said shaft member and including a cylindrical end portion, wherein said locking member is movable between a first position and a second position, wherein a central axis of the cylindrical end portion ~~that is~~ generally coaxial to said shaft member when the locking member is in the first position and ~~a second position that is~~ generally perpendicular to said shaft member when the locking member is in the second position; and

retention means that secures said locking member in said first position and said second position.

2. (Original) The integrated pin and clip of claim 1 further comprising an angled end portion located at a second end of said shaft member.

3. (Withdrawn) The integrated pin and clip of claim 1 further comprising an enlarged portion located at a second end of said shaft member.

4. (Withdrawn) The integrated pin and clip of claim 1 wherein said locking member is rotated about a pivot pin between said first and second positions.

5. - 7. (Canceled).

8. (Original) The integrated pin and clip of claim 1 further comprising a set of nubs located on said shaft member.

9. (Canceled).

10. (Withdrawn) The integrated pin and clip of claim 1, wherein said locking member is a clip that is held in a recessed area by spring.

11. (Withdrawn) The integrated pin and clip of claim 10 wherein said spring applies a force on said clip securing the clip to the shaft member and wherein force must be applied in a direction away from said shaft member to allow the clip to move to and from said first and second positions.

12. (Currently amended) An integrated pin and clip comprising:

a shaft member;

a locking member movable between a first position and a second position, wherein said first position allows for insertion and removal of the integrated pin and clip into a receiving hole and said second position does not allow for insertion and removal of the integrated pin and clip into a receiving hole; and

retention means that secures said locking member in said first position and said second position,

wherein the shaft member includes at least one cut-out portion on an outer surface sized to receive the locking member in seating engagement and retain the locking member in the second position.

13. (Original) The integrated pin and clip of claim 12 further comprising an angled end portion located at a second end of said shaft member.

14. (Withdrawn) The integrated pin and clip of claim 12 wherein said locking member is rotated about a pivot pin between said first and second positions.

15. - 17. (Canceled).

18. (Original) The integrated pin and clip of claim 12 further comprising a set of nubs located on said shaft member.

19. (Canceled).

20. (Withdrawn) The integrated pin and clip of claim 1, wherein said locking member is a clip that is held in a recessed area by spring.

21. (Withdrawn) The integrated pin and clip of claim 20 wherein said spring applies a force on said clip securing the clip to the shaft member and wherein force must be applied in a direction away from said shaft member to allow the clip to move to and from said first and second positions.

22. (Canceled).

23. (New) The integrated pin and clip of claim 1, wherein the cylindrical end portion includes at least one indented region to assist in gripping the locking member.

24. (New) The integrated pin and clip of claim 12, wherein the shaft member includes three cut-out portions disposed approximately 90° apart from each other.

25. (New) The integrated pin and clip of claim 12, wherein the at least one cut-out portion is disposed along a slot in the shaft member.

26. (New) The integrated pin and clip of claim 12, wherein the locking member is adapted to be pulled out of engagement with the at least one cut-out to allow the locking member to be rotated from the second position to the first position.

27. (New) An integrated pin and clip comprising:

a shaft member;

a locking member located at a first end of said shaft member, wherein said locking member is movable between a first position that is generally coaxial to said shaft member and a second position in which the locking member extends laterally from only one side of said shaft member; and

retention means that secures said locking member in said first position and said second position.

28. (New) The integrated pin and clip of claim 27, wherein the locking member is generally perpendicular to the shaft member when in the second position.

29. (New) The integrated pin and clip of claim 27, wherein a portion of the locking member that extends laterally from the shaft member in the second position is cylindrical.

30. (New) The integrated pin and clip of claim 27, wherein the shaft member includes at least one cut-out portion on an outer surface sized to receive the locking member in seating engagement and retain the locking member in the second position.

31. (New) The integrated pin and clip of claim 30, wherein the locking member is adapted to be pulled out of engagement with the at least one cut-out to allow the locking member to be rotated from the second position to the first position.